

2/ports

## INFLATABLE SUPPORT

In order to provide easier user entry, exit or transfer and prevent the user falling out with such an inflatable support, it is known to have two inflatable side chambers extending lengthwise of the support and each connected to receive air under pressure from a source. The source also supplies air under pressure to a plurality of side-by-side alternately inflated air tubes extending laterally of the mattress and between the two side chambers, the arrangement being such that, when inflated, the upper surface of each side chamber lies at or above the upper surface of the air tubes.

However, the above arrangement provides for increased interface pressure at the surface of the side chambers and has resulted in pressure sores occurring on the user at the elbows and heels. Also, the side chambers increase the height of the support making it difficult for some users to physically get onto the support.

The present invention provides an improved inflatable support having stable user entry, exit or transfer from a bed or seat but also providing improved pressure relief over the whole surface area of the support.

According to the invention, an inflatable support for providing pressure relief, comprising at least one inflatable cell extending transversely of the support, the one or more transverse cell(s) having within each of their outermost opposite ends, internal cells at a higher pressure than the transverse cell(s), the internal cells having a lower height than the transverse cells, such that the whole of the support surface provides pressure relief. By arranging for the height of the internal cell

to be smaller than the transverse cell, the pressure relief is not compromised by ensuring that the area enjoying pressure relief is the whole surface of the support. Further, the internal cells provide improved stability of the support edge, so that a user is prevented from falling out and has a firmer edge for entry, exit and transfer.

Preferably, there are provided a plurality of transverse cells inflated and deflated alternately.

More preferably, the internal cells are constantly inflated. To provide a better comfort for the user lying thereon and better pressure relief, the internal cells are chamfered at their internal edges. More preferably, the internal cells are filled with foam or similar material.

Preferably, the internal cells at each opposite end of the transverse cell are connected by a common manifold and inflated jointly by that manifold. Additionally, the manifold is of foam.

The invention will now be described by way of example only with reference to the accompanying figures in which:-

Figure 1 is a schematic view of a pressure pad according to the invention;

Figure 2 is a cross-sectional representation of the pressure pad showing the internal cells; and

Figure 3 is a cross-sectional representation of the pressure pad showing the internal cells and common manifold;

Referring to Figure 1, a first set of inflatable cells 1 and a second set of inflatable cells 2 are shown,

the first set being fully inflated and the second set fully deflated. The two sets are alternately inflatable and are supplied with air from a compressor (not shown). The first and second sets are supplied air from  
5 respective feed lines 7 and 8.

There is provided a base sheet 3 of plastics material to which may be attached restraining straps 4 of plastics material, each cell being retained in position by at least one such strap 4. Adjacent straps are  
10 attached to one another by welds. As shown in Figures 2 and 3, an internal cell 5 is attached between the sides of each cell 1 or 2 at opposite ends.

The transverse cells 1, 2 are generally tubular and of approximately constant cross-section, with height  
15 greater than width on full inflation. The internal cells 5 are positioned at about 2/3 of the height of the inflated cell 1, 2 so that the upper region of the transverse cell 1, 2 over the internal cells 5 provides pressure relief when inflated. The cross sectional shape  
20 of each internal inflated cell is preferably a rectangle with a chamfered internal upper edge. By arranging for the height of the internal cell 5 to be smaller than the transverse cell, the pressure relief is not compromised whilst also providing improved stability at the support  
25 edges. In addition, the chamfered inner edge provides a better comfortable position for the user and ensures that the area enjoying pressure relief is the whole surface of the support. The quasi-rectangular shape of each internal cell 5 is also very much more rigid than the  
30 transverse cells 1, 2.

Each transverse cell 1, 2 is made from a rectangular sheet approximately 51 cm x 89 cm. A rectangular

membrane measuring approximately 3.1 cm to 5 cm x 86 cm is radio frequency welded to one side of the sheet so that when the sheet is folded in half along the shorter side, and welded together along the three pairs of edges, internal cells 5 having a height at about 70% of the height of the transverse cell 1, 2 are welded to the two ends.

An aperture for the passage of air from the respective feed line may be formed in each internal cell 5 and on the transverse cell 1, 2 side end.

In the preferred embodiment, the internal cells 5 are supplied with fluid by manifolds 9, 10 which run along the side of the transverse cells 1, 2. Two such manifolds are shown in Figure 2, one manifold feeding each set of cells 1,2 and opposite internal cells 5. As shown in Figure 3, an additional manifold 12 may be located between each internal cell 5 reducing the number of feeds to the internal cells 5. The internal cells 5 may be filled with foam rather than air to provide a firm outer edge for each transverse cell 1, 2. The two 'foam' internal cells 5 may also be interconnected with foam to prevent the patient from bottoming in the event of power failure or transportation.

The transverse cells 1,2 may be inflated alternately or constantly to provide an alternating or static support surface. The top surface of the transverse cells 1,2 may be perforated to provide a low air loss pad or mattress or seat.